

ALUMINIUM SULPHATE LIQUID

COMMON NAME	Alum Liquid																
DESCRIPTION	Aluminium sulphate is a clear, odourless solution. The liquid is slightly viscous as is manufactured to the Germany's Drinking Water Guidelines specifications.																
TYPICAL SPECIFICATION	<table border="0"> <tr> <td>Aluminium Oxide (% w/w)</td> <td>>7.5</td> </tr> <tr> <td>Hydrated Aluminium Sulphate (%)</td> <td>44% w/w, 57% w/v</td> </tr> <tr> <td>Insoluble (%)</td> <td><0.2</td> </tr> <tr> <td>Arsenic (mg/kg)</td> <td><5</td> </tr> <tr> <td>Chromium (mg/kg)</td> <td><35</td> </tr> <tr> <td>Iron (mg/kg)</td> <td><65</td> </tr> <tr> <td>Lead (mg/kg)</td> <td><7</td> </tr> <tr> <td>Mercury (mg/kg)</td> <td><1</td> </tr> </table>	Aluminium Oxide (% w/w)	>7.5	Hydrated Aluminium Sulphate (%)	44% w/w, 57% w/v	Insoluble (%)	<0.2	Arsenic (mg/kg)	<5	Chromium (mg/kg)	<35	Iron (mg/kg)	<65	Lead (mg/kg)	<7	Mercury (mg/kg)	<1
Aluminium Oxide (% w/w)	>7.5																
Hydrated Aluminium Sulphate (%)	44% w/w, 57% w/v																
Insoluble (%)	<0.2																
Arsenic (mg/kg)	<5																
Chromium (mg/kg)	<35																
Iron (mg/kg)	<65																
Lead (mg/kg)	<7																
Mercury (mg/kg)	<1																
SUPPLY DETAILS	<p>Bulk supply delivered in dedicated tankers.</p> <p>IBC filling available.</p>																
RECOMMENDED STORAGE	<p>Store bags in a dry area out of direct sunlight.</p> <p>Please refer to SDS for detailed storage info.</p>																
SAFETY INFORMATION	Please refer to our current SDS (https://uctr-gmbh.de)																

For further information, please contact our Sales team
info@uctr-gmbh.de WhatsApp: +49-1521-719-3144

Version: 24.04.19